



## TECHNICAL DATA

- with temperatures < 5°C.
- » Inside application: allow sufficient ventilation in case of high humidity level inside the building;
- » Cleaning material: immediately after use with water;
- » Remove OMNIGUARD NF protection film at the end of construction works.
  
- » View: white liquid; light transparent protection film after drying;
- » Indicative consumption:
  - Glass surfaces: 0,4 - 0,6 kg/m<sup>2</sup>
  - Window profiles: 0,6 kg/m<sup>2</sup>
  - Other surfaces: 0,4 - 0,6 kg/m<sup>2</sup>
- » Density : +/- 0,95 kg / L;
- » Weather resistant: after 4 to 48 hours (depending conditions)
- » Storage: 5 – 20 °C; store out of direct sunlight;
- » Conservation: 12 months from date of production in unopened and original packaging;

## PACKAGING

10kg pail - Pallet: 44 x 10 kg (europallet)

## SAFETY

Consult the safety data sheet prior to application. Requested to wear eye protection, mouth mask, gloves and safety wear during application.

## EXTRA

- » Do not hesitate to contact us for further technical information about OMNIGUARD NF.
- » SPI Performance Coatings cannot be held liable for damages on surfaces protected with OMNIGUARD NF.

DATE OF THIS EDITION: 12/06/2018

Our general conditions of sale apply. This document does not have a contractual value. This technical data sheet replaces and annuls the previous edition. The information given in this sheet has the purpose to inform and advice you. At every moment, this sheet can be adapted because of technical evolution. All information is given in good faith and without any warranty. The application, use and processing of these products are beyond our control and therefore the entire responsibility of the user/client/applicator. The user of the product must test the product's suitability and apply for the intended purpose. Established liability if any for any reason is always limited to the value of the goods supplied by SPI Performance Coatings. The products and systems are manufactured under total quality management. SPI Performance Coatings reserves the right to change the properties of its products. Users must always refer to the most recent issue of the local Product Data Sheet, copies of which will be supplied on request.